



Manufactured by



PETROQUIM S.R.L.

Av. Nicolas de Ovando No. 334, Sto. Dgo., Rep. Dom.Tel. (809) 565-2141; Fax: (809) 549-7470 / 567-0330

TECHNICAL DATA SHEET

Servus® 11003

Servus® 11003 is a PVC injection molded overboot. This PVC compound is formulated for long-lasting wear and durability. Supersized overboots fit over large work and recreational footwear to protect them from liquids, dirt, mud and other deteriorating elements.

Features

- Seamless, injection molded PVC 100% waterproof
- Color Black, 4 inches tall
- Available in size: XSM – SML – MED – LRG - XLG
- Extra large molded kick-off lugs for easy, hands-free removal
- Boot buttons are molded to eliminate seams, providing waterproof protection
- Over-sized design to fit over work boots to protect them from harsh environments, increasing the longevity of expensive footwear
- Closure loops tabbed to allow for easy, one-handed closure even when wearing gloves
- SF PVC compound allow for stretchy top and durable outsole



Physical Properties

| Property | Method | Units | Values |
|------------------|---------------|--------------------|-----------|
| Hardness, 15 Seg | ASTM D2240-97 | Shore A | 56±3 |
| Specific Gravity | ASTM D-792 | g/cm ³ | 1.19±0.02 |
| Elongation | ASTM D-412 | % | ≥300 |
| Tension | ASTM D-412 | Kg/cm ² | ≥90 |
| Abrasion DIN | DIN 53-516 | mm ³ | ≤200 |



Quality Assurance Director

Manufacturing Director