



Manufactured by



PETROQUIM S.R.L.

Av. Nicolas de Ovando No. 334, Sto. Dgo., Rep. Dom.Tel. (809) 565-2141; Fax: (809) 549-7470 / 567-0330

TECHNICAL DATA SHEET

Servus® 18805

Servus® 18805 is a PVC injection molded work boot that combines flexible, comfortable uppers with durable hard-wearing outsoles. Integrated with the Iron Duke® soling technology with its characteristics resisting degradation from agricultural chemicals, fertilizers and animal waste, the boot stays flexible, even at colder temperatures.

Features

- Seamless, injection molded PVC 100% waterproof
- Color Brown / Black, 15 inches tall
- Meets ASTM F2892-18 EH
- Meets ASTM F3445-21 Slip Resistance
- Men's Whole Sizes: 3-13 » Fits Women's Sizes: 5-11
- Flexible and durable upper that allows for ease in movement for greater worker comfort
- Reinforced construction at critical stress points provides a durable and long wearing boot
- Deep angle cleat outsole helps to grip slick surfaces to help prevent slips and falls
- FOOT FORM™ contour cushion insoles that are removable, washable and replaceable
- Easy guide along the shaft to customize the boot height at your convenience



Physical Properties

Property	Method	Units	Values
Hardness, 15 Seg	ASTM D2240-97	Shore A	56±3
Specific Gravity	ASTM D-792	g/cm ³	1.19±0.02
Elongation	ASTM D-412	%	≥300
Tension	ASTM D-412	Kg/cm ²	≥90
Abrasion DIN	DIN 53-516	mm ³	≤200



Quality Assurance Director

Manufacturing Director