



Manufactured by



PETROQUIM S.R.L.

Av. Nicolas de Ovando No. 334, Sto. Dgo., Rep. Dom.Tel. (809) 565-2141; Fax: (809) 549-7470 / 567-0330

## TECHNICAL DATA SHEET

**Servus® 22114**

Servus® 22114 is a Neoprene Dipped highly specialized safety boot. Boots begin with hand laid natural rubber to ensure flexibility and strengthen at critical stress points. The boots are then triple dipped in neoprene to create seamless, liquid-tight footwear. The outsole, foxing and top binding are added, and the entire boot is vulcanized to heat-seal the boot together for a 100% seamless waterproof footwear.

### Features

- 100% waterproof seamless construction
- Color Copper / Tan, 12 inches tall
- Meets ASTM F2413-18 M/I/C EH
- Meets ASTM F3445-21 Slip Resistance
- Men's Whole Sizes: 3-15
- Steel Toe footwear to ensure protection and resistance
- Unique dipping process makes boots soft and pliable for less leg fatigue
- Chevron self-cleaning outsole that provides surface-to-surface tread patterns for enhanced grip
- Open channels serve to "squee-gee" liquids, fats and debris out with each step
- Highly resistant to many organic and inorganic acids, chemicals and contaminants
- Fabric linings are soft and durable
- Removable Breathaprene® insoles provide shock absorption and wick away moisture to keep feet dry



### Physical Properties

Property	Method	Units	Values
Elongation	ASTM D-412	%	≥400
Tension	ASTM D-412	Kg/cm <sup>2</sup>	≥90
Abrasion DIN	DIN 53-516	mm <sup>3</sup>	≤300



Quality Assurance Director

Manufacturing Director