



Manufactured by



PETROQUIM[®] S.R.L.

Av. Nicolas de Ovando No. 334, Sto. Dgo., Rep. Dom.Tel. (809) 565-2141; Fax: (809) 549-7470 / 567-0330

TECHNICAL DATA SHEET

Servus Pro+[®] 75105

Servus Pro+[®] 75105 features TDT[™] innovations and an advanced outsole tread system with an aggressive tread along the perimeter and a highly slip-resistant tread along the mid-foot and heel, maximizing surface area contact, helping to prevent hydroplaning.

Features

- Seamless, injection molded PVC 100% waterproof
- Color Grey / Yellow / Beige, 15 inches tall
- Meets ASTM F2413-18 M/I/C EH
- Meets ASTM F3445-21 Slip Resistance
- Men's Whole Sizes: 3-15 » Fits Women's Sizes: 5-12
- Steel Toe footwear to ensure protection and resistance
- Outsole perimeter is formulated for tough, long wearing support
- Extra thick toe and heel guards protect against abrasion and wear
- Centersole is dual compounded for cushioning, long wear and traction on slick surfaces
- Steel shank is longer, wider, and thicker for outstanding arch support
- FOOT FORM[™] contour cushion insoles that are removable, washable and replaceable



Physical Properties

Property	Method	Units	Values
Hardness, 15 Seg	ASTM D2240-97	Shore A	56±3
Specific Gravity	ASTM D-792	g/cm ³	1.19±0.02
Elongation	ASTM D-412	%	≥300
Tension	ASTM D-412	Kg/cm ²	≥90
Abrasion DIN	DIN 53-516	mm ³	≤200



Quality Assurance Director

Manufacturing Director