



Manufactured by



PETROQUIM S.R.L.

Av. Nicolas de Ovando No. 334, Sto. Dgo., Rep. Dom.Tel. (809) 565-2141; Fax: (809) 549-7470 / 567-0330

TECHNICAL DATA SHEET

Servus® 75120

Servus® 75120 features TDT™ innovations and a compound blend engineered to withstand degradation from harsh chemicals. Its MAX series dual PVC outsole generates a perimeter for abrasion and long wear helping to prevent slip and trip hazards, while the center sole is softer to allow more surface-to-surface contact to control traction on slick surfaces.

Features

- Seamless, injection molded PVC 100% waterproof
- Color Olive / Green / Black, 15 inches tall
- Meets ASTM F2892-18 EH
- Meets ASTM F3445-21 Slip Resistance
- Men's Whole Sizes: 3-15 » Fits Women's Sizes: 5-12
- Outsole perimeter is formulated for tough, long wearing support
- Centersole is dual compounded for cushioning, long wear and traction on slick surfaces
- Steel shank is longer, wider, and thicker for outstanding arch support
- FOOT FORM™ contour cushion insoles that are removable, washable and replaceable
- Open pattern outsole design self-cleans liquid and debris with every step



Physical Properties

Property	Method	Units	Values
Hardness, 15 Seg	ASTM D2240-97	Shore A	56±3
Specific Gravity	ASTM D-792	g/cm ³	1.19±0.02
Elongation	ASTM D-412	%	≥300
Tension	ASTM D-412	Kg/cm ²	≥90
Abrasion DIN	DIN 53-516	mm ³	≤200



Quality Assurance Director

Manufacturing Director