



Manufactured by



PETROQUIM S.R.L.

Av. Nicolas de Ovando No. 334, Sto. Dgo., Rep. Dom.Tel. (809) 565-2141; Fax: (809) 549-7470 / 567-0330

## TECHNICAL DATA SHEET

**Servus® 75145C**

Servus® 75145C is a PVC injection molded boot that features exceptional comfort and function at a value price. This PVC formulation is resistant to degradation from agricultural chemicals, fertilizers and animal waste. Ideal for food processing, custodial, and general purpose industries.

### Features

- Seamless, injection molded PVC 100% waterproof
- Color Black / Orange, 15 inches tall
- Meets ASTM F2413-18 M/I/C EH PR
- Meets ASTM F3445-21 Slip Resistance
- Meets CSA Grade 1 Steel Toe ESR Sole Puncture Protection
- Men's Whole Sizes: 7-14
- Steel Toe footwear to ensure protection and resistance
- Steel shank is longer, wider, and thicker for outstanding arch support
- Flexible and durable upper that allows for ease in movement for greater worker comfort
- Reinforced construction at critical stress points provides a durable and long wearing boot
- Flexible steel midsole for puncture protection and steel shank
- Deep angle cleat outsole helps to grip slick surfaces to help prevent slips and falls
- Open pattern, self-cleaning outsole design clears liquid and debris with every step
- FOOT FORM™ contour cushion insoles that are removable, washable and replaceable
- Easy guide along the shaft to customize the boot height at your convenience



### Physical Properties

Property	Method	Units	Values
Hardness, 15 Seg	ASTM D2240-97	Shore A	56±3
Specific Gravity	ASTM D-792	g/cm <sup>3</sup>	1.19±0.02
Elongation	ASTM D-412	%	≥300
Tension	ASTM D-412	Kg/cm <sup>2</sup>	≥90
Abrasion DIN	DIN 53-516	mm <sup>3</sup>	≤200



Quality Assurance Director

Manufacturing Director

